

Ergo-Glass for Profile (EGP)

EGP: Ergo-Glass for Profiles; Lifting Capacity: 30/60 Kg

The Ergo-Glass end effector that, when integrated in Quick-Lift System[®], meets the highest standards of ergonomics, working environment, safety and efficiency.

Easy to use, thanks to outstanding responsiveness, regardless of load weight. High cost efficiency through built in energy save function, high reliability and long durability.


The sensitive manoeuvre handle provides the operator a precise and controlled movement of the glass panel.

Developed to handle parts for the window frame during manufacturing. Designed with a combination of pneumatic grip and vacuum. Function is quickly altered by pushing a button.

Modular design of the vacuum suction interface creates unlimited possibilities for customized solutions.

Maximum security due to a combination of sound and visual alarms activated in case of pressure drop or lack of vacuum.

With integrated “anti-drop” and energy saving as standard this end effector provides a first class solution.







BINAR

Improving your productivity

Ergo-Glass for Profile (EGP)

EGP: Ergo-Glass for Profiles; Lifting Capacity: 30/60 Kg

The figures are to be seen as indications and may vary depending on handling application.



TECHNICAL DATA

Description	<p>Equipped with fixed suction cups.</p> <p>The control handle provides a logic and simple interface for the operator for up and down movement as well push buttons for grip and release of the glass panels.</p> <p>The control box at the top provides setting of adjustable speed depending of the application.</p> <p>The control box at the top provides setting of adjustable speed depending of the application.</p> <p>Both grip or suction function to maximize lifting options of profiles.</p>
Lifting capacity	Profiles : 30/60 kg depending on configuration of the suction cups.
End effector weight	End effector weight somewhere between 30-80 kg, depending on end effector's size and lifting capacity.
Air supply	Clean dry air, pressure 6-8 bar.
Safety	<p>All suction cups with a safety factor of 4.</p> <p>Both audio (buzzer) and visual (red lamp) indication when insufficient vacuum.</p> <p>Up movement is automatically restricted when too low vacuum is detected.</p> <p>Load is continuously supervised by the Quick-Lift and can only be released once end effector is landed on surface.</p>
Options	Vacuum tank (in case of insufficient vacuum).
Manoeuvring	Manoeuvring is done with Binar Handlings patented control handle. Only a small force is needed to engage the up/down motion. When the operator let go of the handle, the up/down motion is immediately stopped.
End effector	End effectors are designed to fit customers need. Intelligent I/O signals are available for optimum functionality.

Binar Handling AB disclaims responsibility for any errors or incomplete information in the published material and reserves the right to make changes

Binar Handling AB

Hedekullevägen 24 • SE-461 38 TROLLHÄTTAN • Sweden
 telephone: +46 (0)520 47 40 00 • e-mail: info.handling@binar.se
 www.binarhandling.com

2021-02-23 EN 3.1

BINAR
 Improving your productivity